




TWS-1815 works as sounder, flasher or both options at the same time according to project needs. It operates with 4pcs CR123A battery and communicates completely wirelessly with the control panel.


It has two different color options, white and red. Supports 3 different sound level along with 3 different flasher mode.

- Comply with EN54-3 and EN54-25
- Up To 500mt Wireless Coverage (Open Area)
- Up To 6 Years Battery Lifetime with 4X CR123A Battery
 Only Sounder, Only Flasher or Both Options can be Operated
- 3 Different Sound Level
- 3 Different Flasher Mode (Slow, Normal, Fast)



T 1 : 10 :0: 0:	TIME 4045
Technical Specifications	
Standard	Comply with EN54-3 and EN54-25
Operating Frequency	868Mhz
RF Power	14dBm (25mW)
Number of Channel	10
Coverage	Up To 500mt (Open Space)
Battery	Up To 6 Years With 4X CR123A Battery
Average Consumption	20μA (@12V)
Sound Level	88,4dB / 90,3dB / 95dB ±2 (@12VDC, 1mt.)
Flasher Coverage	W-2,4-4
Sounder Mode	3 Modes (Low-Mid-High)
Sounder Tone Options	42 Different Tone
Flasher Mode	3 Modes (Slow-Normal-Fast)
Operating Temperature	-10°C ~ 55°C
Color and Body Material	RED / White - UL94 non-flammabilityPolycarbonate
Dimensions (mm)	Ø:110mm, h:55mm (Includes Base)
Wight	190gr. (Without Battery)
Humidity	95% RH
Protection Class	IP21C





Link/Test Button CR123A Battery Tamper Switch

Programming Connector