

TPU-9243P

External Power Supply, 24VDC 3,5Ah, Plastic Case

TPU-9243P is designed to use in systems where required external power supply by providing 24VDC 3,5Ah uninterrupted power with an intelligent battery charger unit and complies with EN 54-4. Both input and outputs of devices are protected against short circuit and overload. The device allows to use 7Ah or 7.2Ah battery options.

General Features

- EN 54-4 certificates
- Selectable Single or Dual Output
- Supports 7Ah or 7.2Ah Backup Battery
- Dry Contact Relay Output for Error
- Led Indicators for Fault
- Intelligent Battery Charging with Temperature Compensation
- Wide Input Voltage Range, 230~115 VAC
- Protection Against Short Circuit and Overload Conditions
- Fully Enclosed and Robust Plastic Case



Technical Specifications

	TPU-9243P
Standard	EN 54-4
Automatic Fused Outputs	Yes
Operating Voltage	230~115 VAC
Operating Frequency	50 Hz - 60 Hz
Output Voltage	20 ~ 24 VDC \pm %2
Number of Outputs	2
Maximum Output Current	3,5A
Outputs (S1 Closed, S2 Open)	Output -1: 3,5A Output -2: 0,0A
Outputs (S1 Open, S2 Closed)	Output -1: 1,75A Output -2: 1,75A
Backup Battery	2x12V, 7Ah - 2x12V, 7.2Ah
Charging Voltage	27.6V @ 20°C
Discharge cut-off	< 20V
Body material and color	Plastic, ABS
Dimensions (mm)	360 x 340 x 108
Weight (Without Battery)	1,767 Kg
IP Class	IP30
Operating Temperature	-10°C ~ +55°C
Humidity	95% RH (max)