teknim[®]





TFM-128X bases can be used with Teknim addressable detectors (TFD-12XX). TFM-128X bases can be in a formed such as isolator, buzzer and flasher which design to meet all needs of warning for the detectors.

GENERAL FEATURES

- LED indicators enabling 360° view
- Two different colors of indication by LEDs to individually display shortcut and alarm conditions (Yellow/Red)
- 75dB sound level
- Different type of base options
- Label tag slot

TYPES

- TFM-1281 Base with Buzzer
- TFM-1282 Base with Flasher
- TFM-1283 Base with Isolator
- TFM-1287 Base with Buzzer and Flasher







Technical Specifications	TFM-1281	TFM-1282	TFM-1283	TFM-1287
Operation	Buzzer	Flasher	Izolator	Buzzer + Flasher
LED Indicator	No	Yes	Yes	Yes
Buzzer	Yes	No	No	Yes
Sound Level	75dB			75dB
Flasher	No	Yes	No	Yes
Power	15-32V	15-32V	15-32V	15-32V
Standby Consumption	15μΑ	15µA	15μΑ	15μΑ
Alarm Consumption	2mA	4mA	15μΑ	6mA
Weight	120gr	120gr	120gr	120gr
Dimensions (mm)	Ø109,5 h48	Ø109,5 h48	Ø109,5 h48	Ø109,5 h48
Body Material and Color	ABS Plastic – White			
Operating Temperature	-10°C ~ +70°C	-10°C ~ +70°C	-10°C ~ +70°C	-10°C ~ +70°C
Humidity	95% RH	95% RH	95% RH	95% RH