



EN54-25 EN54-11 EN54-13

TWB-1866 is a wireless manual call point used to create manual warning in case of fire. It communicates completely wirelessly with the control panel.


TWB-1866 can operate 4 years with single battery or 8 years with two battery. It supports resettable type of operation and additional protection cover can be implemented to avoid situations that may cause false alarms.

GENERAL FEATURES

- EN54-11 and EN 54-25 Certified
- Up To Approx. 500mt Wireless Coverage (Open Area)
- Up To 8 Years Battery Lifetime with Two CR123A Battery
- Resettable Type of Operation
- Optional Protection Cover
- Flush or Surface Mounting Option

Technical Specifications	TWB-1866
Standard	EN54-11 and EN54-25
Operating Frequency	868mHz
RF Power	14dBm (25mW)
Number of Channel	10
Coverage	Up To 500mt (Open Space)
Battery	Up To 8 Years With 2X CR123A Battery
Average Consumption	25μΑ
Operation Type	Resettable
Operating Temperature	-10°C ~ 55°C
Dimensions (mm)	86x55x88 mm
Humidity	95% RH
Protection Class	IP30






Programming Connector

Tamper Switch Link/Test Button

CR123A Battery



88.5mm

.0

0

88.8mm



- 55.7mm →